

SERIES 550

DV217
SILK OAK



DX801
FROSTED WHITE



DV189
URBAN MIX GREY
WHITE



DV011
GREY ASH



DV819
URBAN MIX LIGHT



DV372
RUSTIC OAK



DV318
VELVET OAK



DV441
LIGHT COUNTRY OAK



Rigid Plank 1219.2 x 228.6 x 4mm / 0.55 + 1.5mm = 5.5mm
Samples are representative of décor and décor pattern.
Please consult www.azura.co.za for clarity on décor and décor pattern.

deZign FLOOR

SERIES 550

DV131
URBAN MIX DARK



DV775
BURNED WOOD PLANK



DV500
MARBLE WHITE
CARRARA



DV520
MARBLE MEDIUM
GREY



DV550
MARBLE CHARCOAL



DV204
CONCRETE LIGHT GREY



DV510
CONCRETE MEDIUM
GREY



Rigid Plank 1219.2 x 228.6 x 4mm / 0.55 + 1.5mm = 5.5mm
Samples are representative of décor and décor pattern.
Please consult www.azura.co.za for clarity on décor and décor pattern.

deZIGN FLOOR

PRODUCT		SERIES 550	
Type	Rigid Board, Click System [UNILIN]		
Construction	Stone Plastic Composite [SPC]		
Application	Residential, Heavy Commercial		
FEATURE		SERIES 550	
Class	Class 33		
Wear Layer	0.55 with Paragon UV Layer		
Core	Equilibrium Core Structure (ECS)		
Bevel Edge	Painted Groove 4V		
Water Tolerance	Water Resistant		
Underlay	1.5mm IXPE Underlay backing		
PACKAGING		WOOD	CONCRETE /MARBLE
m ² per pack	2.23m ²	2.553m ²	
Planks per pack	9	9	
Packs per pallet	60	60	
Weight per Pack (Kg)	20,40	17,40	
DIMENSIONS		WOOD	CONCRETE /MARBLE
Plank Size (mm)	228.6 x 1219.2	465 x 915	
Plank Thickness (mm)	4 x (SPC) + 1.5 x (IXPE Underlay)	4 x (SPC) + 1.5 x (IXPE Underlay)	
Total Thickness (mm)	5.5	5.5	
WARRANTY		SERIES 550	
Residential	25 years		
Commercial (limited to application)	15 years		
PRODUCT SERIES		SERIES 550	
Product Description	deZIGN Floor Series 550		
Range	deZign SPC Floor		
TECHINCAL DATA			
Classification	Class 33 / 0.55		
Wear Resistance	IP - 4000 cycles		
Abrasion	0.15		
Abrasion Resistance	Group T		
PCP	Not Detected		
Colour Fastness to Light	Minimum 6		
Slip Resistance	R10		
Fire Classification	Bfl-S1		
Phtalate Test	Not Detected		
ROHS	Not Detected		
Staining Resistance	Not A ected		
Dimensional Stability	Short 0.02; Length 0.04		
Squareness	Short 0.03; Length 0.09		
Length	0.25		
Width	0.15		
Thickness	0.15		
Peel Strength	0.3mm 58N		
E ect of a Castor Chair	No Visible Damage		
VOC Emission	Pass		
Residual Indentation	0.40%		
Resistant to Chemicals	No Change		
Resistance to Hear	0.49		
Resistant to Light	0.87		
Static Coe ficient to Friction	Dry 0.94; Wet 0.68		
Static Load Resistance	0.04		
Thermal Conductivity	0.163		
Thermal Resistance	0.033		
Materials	100% Virgin Materials		
Sound Insulation material performance test	STC=72		



Rigid Plank 1219.2 x 228.6 x 4mm / 0.55 + 1.5mm = 5.5mm

Samples are representative of décor and décor pattern. Please consult www.azura.co.za for clarity on décor and décor pattern.